

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 2001012573 A

(43) Date of publication of application: 16.01.01

(51) Int. Cl. F16H 15/38

(21) Application number: 11183247

(22) Date of filing: 29.06.99

(71) Applicant: NSK LTD

(72) Inventor:
ISHIKAWA HIROSHI
IMANISHI TAKASHI
ITO HIROYUKI

(54) TOROIDAL TYPE, CONTINUOUSLY VARIABLE TRANSMISSION

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a toroidal type continuously variable transmission capable of suppressing the lowering of a power transmission efficiency and also suppressing an increase of size.

SOLUTION: A toroidal type continuously variable transmission 30 comprises an input shaft 1, an input disk 2a, an output disk, and a hydraulic loading mechanism 6. The input shaft 1 and input disk 2a are rotated by a drive source E. The hydraulic loading mechanism 6 comprises cylinders 41 and 59 and disk members 60 and 61. A space surrounded by the inner peripheral surface of the cylinder 59, a bottom surface 65 of a disk member 60, and a rear surface 42a of the input disk 2a forms a first hydraulic chamber 67. A space surrounded by the inner peripheral surface of the cylinder 59, a bottom surface 48a of the cylinder 41, and an end surface 69 of the disk member 61 forms a second hydraulic chamber 70. In the

hydraulic chamber 67 and 70, pressure oil is supplied to press the input disk 2a toward the output disk.

COPYRIGHT: (C)2001,JPO

